



Produkteigenschaften

Form	rund, mit Trafo
Länge inkl. Trafotunnel	580 mm
Breite	404 mm
Einbauöffnung	individuell bis 300 mm
Gesamthöhe	140 mm
Farbe	schwarz
Anzahl Rohreinführungen	2 x M20 und 2 x M25
Zugentlastung	Nein

Betoneinbaugehäuse XL Flex 300 mit Trafo - Ein betondichtetes Einbaugehäuse für Ortbeton

- » Für Ortbeton
- » Membrantechnik
- » Werkzeuglose Rohreinführung M20/M25
- » Absolut betondicht
- » Mit Trafotunnel

Serie	-
Artikelnummer	P536
Kategorie	Betoninstallation
Montageart	Nagel, Kleber
Einsatz	Ortbeton
EAN	4260182061039

Materialeigenschaften

Material Gehäuse	PP
Material Einführung	TPE



XL 300 Flex Installation housing with tunnel - A concrete-tight installation housing for cast-in-place concrete

- » For cast-in-place concrete and prefabrication
- » Membrane technology
- » Toolless conduit insertion M20/M25
- » Absolutely concrete-tight
- » With tunnel



Product features

Shape	round with tunnel
Length incl. tunnel	580 mm
Wide	404 mm
Installation opening	individual till 300 mm
Total height	140 mm
Color	black
Number of conduit entries	2 x M20 and 2 x M25
Strain relief	No

Series	-
Article No.	P536
Category	Concrete installation
Type of installation	Nail, glue
Use	Cast-in-place concrete
EAN	4260182061039

Material properties

Material housing	PP
Membrane material	TPE