



Produkteigenschaften

| | |
|-------------------------|------------------------|
| Form | rund, mit Trafo |
| Tiefe | 120 mm |
| Einbaudurchmesser | Individuell bis 300 mm |
| Gesamthöhe | 120 mm |
| Gehäusedurchmesser | 320 mm |
| Farbe | schwarz |
| Anzahl Rohreinführungen | 2 x M20 und 2 x M25 |
| Zugentlastung | Nein |

Betoneinbaugehäuse XL 300 - Ein betondichtetes Einbaugehäuse für Ortbeton und Werksfertigung

- » Für Ortbeton und Werksfertigung
- » Membrantechnik
- » Werkzeuglose Rohreinführung M20/M25
- » Absolut betondicht
- » Ohne Trafotunnel
- » Mit Mineralfaserplatte

| | |
|---------------|---------------------------|
| Serie | - |
| Artikelnummer | P606 |
| Kategorie | Betoninstallation |
| Montageart | Nagel, Kleber |
| Einsatz | Ortbeton , Werksfertigung |
| EAN | 4260182062180 |

Materialeigenschaften

| | |
|---------------------|-----|
| Material Gehäuse | PP |
| Material Einführung | TPE |



Product features

| | |
|---------------------------|------------------------|
| Shape | round with tunnel |
| Depth | 120 mm |
| Installation diameter | Individual till 300 mm |
| Height | 120 mm |
| Housing diameter | 320 mm |
| Color | black |
| Number of conduit entries | 2 x M20 and 2 x M25 |
| Strain relief | No |

XL 300 installation housing - A concrete-tight installation housing for cast-in- place concrete and prefabrication

- » For cast-in-place concrete and prefabrication
- » Membrane technology
- » Toolless conduit insertion M20/M25
- » Absolutely concrete-tight
- » Without tunnel
- » With mineral fibre board

| | |
|----------------------|---|
| Series | - |
| Article No. | P606 |
| Category | Concrete installation |
| Type of installation | Nail, glue |
| Use | Cast-in-place concrete, prefabrication |
| EAN | 4260182062180 |

Material properties

| | |
|-------------------|-----|
| Material housing | PP |
| Membrane material | TPE |