



Produkteigenschaften

Einbautiefe	70 mm
Außendurchmesser	68 mm
Auslassöffnung	66 mm
Leuchteneinbauhöhe	67 mm
Klappenlänge	50 mm
Klappenbreite	26 mm
Rand Lampenöffnung	5 mm
Stärke Kappe	0,8 - 1,0 mm
Lampenleistung max.	35 W
Farbe	transparent

Schutzkappe Niedervolt / LED 68 mm - Für aktiven Schutz in Hohldecken

- » Keine Brandgefahr
- » Intakte Dampfsperre
- » Lebensdauer der Leuchtmittel gewährt
- » Optimal geeignet für Halogeneinbaustrahler, LED
- » Einfacher, nachträglicher Einbau
- » Schützt LED vor Überhitzung
- » Aktiver Brandschutz
- » Nicht geeignet für Kaltlichtlampen

Serie	-
Artikelnummer	P008-D
Kategorie	Brandschutz
Montageart	-
Einsatz	Deckenbeleuchtung
EAN	4260182060148

Materialeigenschaften

Material	Silikon-Kautschuk
----------	-------------------



**Protective cap low voltage / LED 68 mm -
For active protection in hallow ceilings**

- » Intact vapor barrier
- » Lifetime of the illuminants guaranteed
- » Ideally suited for recessed halogen spotlights, LED
- » Easy retrofit installation
- » Protects LED from overheating
- » Active fire protection
- » Not suitable for cold light lamps

Product features

Installation depth	70 mm
Outer diameter	68 mm
Outlet opening	66 mm
Luminaire installation height	67 mm
Flap length	50 mm
Flap width	26 mm
Edge lamp opening	5 mm
Thickness cap	0,8 - 1,0 mm
Lamp power max.	35 W
Color	transparent

Series	-
Article No.	P008-D
Category	Fire protection
Type of installation	-
Use	ceiling lighting
EAN	4260182060148

Material properties

Material	Silicone-rubber
----------	-----------------