



Installationsdose - Wärmedämmungsdose zur Installation von Geräten in wärme gedämmten Fassaden

- » Für jede Dämmungsstärke geeignet
- » Keine Kältebrücke durch integrierte Dämmung
- » Sicherer Halt aller elektrischen Geräte auf der Dämmung

Serie	-
Artikelnummer	P429
Kategorie	Unterputzinstallation
Montageart	Nagel
Einsatz	WDVS Elektroinstallation
EAN	4260182062098

Produkteigenschaften

Tiefe	45 mm
Außenmaße	120 x 120 mm
Isolierstärke	50 - 200 mm
Querschnitt ohne Gerät (1,5 mm)	6 Klemmen, 20 Leiter
Querschnitt ohne Gerät (2,5mm)	5 Klemmen, 15 Leiter
Brandklasse	A1 - F
Temperaturbereich	-25 °C bis + 60 °C
Farbe	grau

Materialeigenschaften

Material	PP (selbstlöschend)
----------	---------------------



Installation box - Thermal insulation box for installation of devices in thermally insulated facades

- » Suitable for any insulation thickness
- » No cold bridge due to integrated insulation
- » Secure hold of all electrical devices on the insulation

Data sheet

Product features

Depth	45 mm
External dimensions	120 x 120 mm
Insulation thickness	50 - 200 mm
Cross-section without device (1,5 mm)	6 clamps, 20 conductors
Cross-section without device (2,5mm)	5 clamps, 15 conductors
Fire classification	A1 - F
Temperature range	-25 °C bis + 60 °C
Color	grey

Series	-
Article No.	P429
Category	Flush mounting installation
Type of installation	Nail
Use	External wall insulation system
EAN	4260182062098

Material properties

Material	PP (self-extinguishing)
----------	-------------------------